


注記

- 1) 嵌合相手品番: 7222-8520-40
7222-8520-70 (7C22-8520-70)
7222-8521-80
- 2) () 内品番は、エンプラツ回線及び、特別管理回路を使用する場合に適用すること。

NOTES

- 1) MATING PART NO. : 7222-8520-40
7222-8520-70 (7C22-8520-70)
7222-8521-80
- 2) () PART NO. IS USED FOR PARTS ASSOCIATED WITH A/B CIRCUITS OR OTHER SPECIFIED CIRCUIT.

97.06.20		ADDED A/B PART NO.	C97-M302	M. T	CUSTOMER		CUSTOMER PART NO.		CUSTOMER DWG NO.		MATERIAL		PBT (NATURAL)		TREAT.		ISSUE MARK		
89.07.03		RENEW	C89-6692	M. K	OFFICE		TRIAL PART NO.				SPEC.		Z-TYPE CONNECTOR 2P M (GY), (BR)		8 FIN.				
LET DATE		REVISION RECORD	NO.	CHKD	VENDOR		VENDOR NO.				NAME		FRONT HOLDER						
GENERAL TOLERANCE																			
10MAX	50MAX	100MAX	250MAX	500V	ANGLE	ECCENT	DWG TYPE	DWG SOURCE	DWG DATE	UNIT	SCL	ANGLE	PART NO.	7157-7728 (7B57-7728)					
A	±0.15	±0.2	±0.3	±0.5	±30'	0.1	R	RENEW	89.07.03	mm	5/1	3	CH. CODE	7157-7728:R					
B	±0.2	±0.3	±0.55	±0.95	±1.4	0.1	APPROVED	CHECKED	CHECKED	DESIGN	DRAWN		DWG NO.	7157-7728:R					
◎	±0.3	±0.5	±0.8	±1.4	±2	0.15	不採用		検査	YASHIMA	SERISAWA		SET DWG NO.						
SPECIFIED										MASS	9	92.06.30	97.6.27	87.02.03	97.06.20				



1

2

3

B

B

A

A

1

2

3