




3

2

1



注記

1. 材質 : 100 °C 雰囲気対応材。

NOTE

1. MATERIAL THAT IS CAPABLE TO BE USED IN 100°C ENVIRONMENT.

A

A

GENERAL TOLERANCE										
10 MAX	50 MAX	100 MAX	250 MAX	R5 MAX	R10 MAX	R20 MAX	R20 OVR	ANGLE	ECCENT	
A	±0.15	±0.2	±0.3	±0.5	±0.75	±0.3	±0.5	±2.5	±3°	0.1
B	±0.2	±0.3	±0.55	±0.95	±1.4	±0.2	±0.5	±3°	±3°	0.1
C	±0.3	±0.5	±0.8	±1.4	±2			±3°	±3°	0.15

CUSTOMER	CUSTOMER PART NO.	CUSTOMER DWG NO.	MATL. SPEC.	SEE NOTE	TREAT. & FIN.
OFFICE	TRIAL PART NO.		NAME	SQUIB 2P FERRITE	

LET	DATE	REVISION RECORD	NO.	CHKD	VENDOR NO.
△	2014/02/11	DELETED A/B PART NO. ETC.	C14-Z068	J. C	
	2011/08/20	NEW	C11-Z542	J. B	

10MAX	50MAX	100MAX	250MAX	250OVR	ANGLE	ECCENT	PART NO.	△7173-1873	
A	±0.15	±0.2	±0.3	±0.5	±0.75	±30'	CH. CODE	△	
B	±0.2	±0.3	±0.55	±0.95	±1.4	±30'	DWG NO.	7173-1873:R	
C	±0.3	±0.5	±0.8	±1.4	±2	±30'	SET DWG NO.		
SPECIFIED							MASS	YAZAKI CORPORATION	

3

2

1