

3

2

1




△	PART NO.	COLOR
	7182-8730-10, △	DARK GRAY
	7182-8730-30, △	BLACK

注 記

- △ 1. 嵌合メス ハウジング品番: 7283-8730-30 ETC.
2. 適用端子品番: 7114-1680-02
3. 適用リヤ-ホルダー品番: 7157-4603-80

NOTES

- △ 1. MATING FEMALE HOUSING NO.
: 7283-8730-30 ETC.
2. APPLICABLE TERMINAL NO.
: 7114-1680-02
3. APPLICABLE REAR HOLDER NO.
: 7157-4603-80



B

A

B

A

△	94.08.30	ADDED COLOR NO. & CHANGED FORM, △	C94-M128	K. S	CUSTOMER CUSTOMER PART NO.	CUSTOMER DWG NO.	MATL. SPEC.	PBT	TREAT. & FIN.	ISSUE MARK							
LET	91.01.10	NEW	C91-L005	S. I	OFFICE	TRIAL PART NO.	NAME	SSD CONNECTOR HOUSING									
DATE	94.09.06	REVISION RECORD	NO.	CHKD	VENDOR	VENDOR NO.	3P MALE										
GENERAL TOLERANCE																	
A	10MAX	50MAX	100MAX	250MAX	2500VR	ANGLE	ECCENT	DWG TYPE	DWG SOURCE	DWG DATE	UNIT	SCL	ANGLE	PART NO.			
A	±0.15	±0.2	±0.3	±0.5	±0.75	±30'	0.1	R	NEW	91.01.10	mm	2/1	3	△ 7182-8730-30 ETC.			
B	±0.2	±0.3	±0.55	±0.95	±1.4	±30'	0.1	APPROVED	CHECKED	CHECKED	DESIGN	DRAWN	DWG NO.	7182-8730-30:R			
(C)	±0.3	±0.5	±0.8	±1.4	±2	±30'	0.15	1/2	石塚	駿島	KANEKO	MASUBUCHI					
SPECIFIED											94.09.06		94.09.05	94.09.05	89.11.01	94.08.30	YAZAKI CORPORATION
											94.09.06		94.09.05	94.09.05	89.11.01	94.08.30	

3

2

1