


1. PARTS MUST BE PURCHASED FROM YAZAKI.
2. PARTS MUST BE FREE OF FLASH AND IMPERFECTIONS THAT AFFECT FUNCTION.
3. APPLICABLE TERMINAL: SEE DRAWING 7116-4110-02R (2.8 YESC UNSEALED)
MAX WIRE OD: 3.70mm
4. MATING PART NUMBER: 7282-6466-40
5. PART SATISFIES GMW 3191 DATE JUNE 2012 (T2/V1/S1/MF3) WITH THE FOLLOWING EXCEPTIONS:
 - 4.2.4 TERMINAL ENGAGE WITH TPA IN FULL-SET POSITION, WIRE SIZE >1.00 mm² =42N MIN
 - 4.2.15.4.2 CPA CLOSING FORCE UNMATED CONNECTOR=103N MIN
6. PART TO COMPLY WITH YPES-31-038 REQUIREMENTS
7. THIS DIMENSION SHOWS THE PRE-SET POSITION OF THE CPA.
8. THIS DIMENSION SHOWS THE PRE-SET POSITION OF THE TPA.
9. THIS DRAWING IS TO BE USED FOR INTERNAL YAZAKI PSW SUBMISSION.
10. HANDLING MANUAL NUMBER: YPES-15-599E

7289-7238-40

$$(7.56) \quad$$
YAZAKI CORPORATION